

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 200028759 B2**
(10) Patent No. **762347**

(54) Title
Toothbrush head with flexibly mounted bristles

(51)⁶ International Patent Classification(s)
A46B 009/10 A46B 003/00

(21) Application No: 200028759 (22) Application Date: 2000 . 02 . 09

(87) WIPO No: WO00/47083

(30) Priority Data

(31) Number (32) Date (33) Country
09/247401 1999 . 02 . 10 US

(43) Publication Date : 2000 . 08 . 29

(43) Publication Journal Date : 2000 . 11 . 02

(44) Accepted Journal Date : 2003 . 06 . 26

(71) Applicant(s)
Colgate-Palmolive Company

(72) Inventor(s)
Douglas J. Hohlbein

(74) Agent/Attorney
F.B. RICE and CO., 139 Rathdowne Street, CARLTON VIC 3053


(56) Related Art
WO 98/35584
US 5836036

28 159/00

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A46B 9/10, 3/00	A1	(11) International Publication Number: WO 00/47083 (43) International Publication Date: 17 August 2000 (17.08.00)
(21) International Application Number: PCT/US00/03333 (22) International Filing Date: 9 February 2000 (09.02.00) (30) Priority Data: 09/247,401 10 February 1999 (10.02.99) US (71) Applicant: COLGATE-PALMOLIVE COMPANY [US/US]; 300 Park Avenue, New York, NY 10022 (US). (72) Inventor: HOHLBEIN, Douglas, J.; 45 Diverty Road, Pennington, NJ 08534 (US). (74) Agent: GOLDFINE, Henry; Colgate-Palmolive Company, 909 River Road, P.O. Box 1343, Piscataway, NJ 08855-1343 (US).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: TOOTHBRUSH HEAD WITH FLEXIBLY MOUNTED BRISTLES (57) Abstract The present invention relates to a toothbrush (10) having bristles mounted on a flexibly resilient lattice network, such that the bristles deflect during brushing to conform to the various arcuate surfaces of the teeth for more effective cleaning thereof.		



**Toothbrush Head
With Flexibly Mounted Bristles**

Field of the Invention

5 The present invention relates to toothbrush heads and more particularly to toothbrush heads having bristles mounted in a flexibly resilient network, such that the bristles deflect to conform to the configuration of the teeth.

Background of the Invention

10 Conventional toothbrushes comprise uniform tufts of bristles each having a first end which is held captive in and fixed to a brush head, and a second end which is free and which is used for brushing. The free
15 ends of the various tufts present a surface envelope which is capable of slight deformation by the bristles bending when they come in contact with a surface to be brushed, but which is incapable of adequately matching a surface having a complex shape with varying levels. Such a complex surface is present in the mouth, wherein the teeth generally lie
20 in a "C" shaped curve within the upper and lower jaw, each row of teeth consequently having a convex outer curve and a concave inner curve. Further, the teeth themselves are contoured in an arcuate shape having significantly varying levels, including a deep "V" shaped interproximal area between one tooth and the next.

25 The desire of users to cause the bristles to conform to the teeth and to penetrate the interproximal spaces between the teeth is expressed by the forceful application of the brush to adequately deform the bristles to the arcuate contours of the dentiture. Such forceful application of the brush
30 against the teeth merely leads to excessive wear of the tooth surfaces

and gums, without adequate conformation of the brush about and between the teeth to provide the desired cleaning.

5 Toothbrushes such as those disclosed in PCT WO 98/35584, having
bristle tufts capable of a toggling movement partially address the above
problem. PCT WO 98/35584 discloses bristle tufts mounted in a
resilient material held within an array of rigid receptacles or wells whose
connection to the overall frame or skeleton of the brush has been
broken. As the tufts are solely connected to the brush by the resilient
10 material they will independently toggle or move in all planes
(upwards/downwards/sideways). However, such independent motion of
the bristles will not cause them to conform to the configuration of the
teeth.

15 U.S. Patent 4,633,542 discloses a toothbrush in which the bristles are
slidably mounted within a rigid head, resting upon a resiliently
deformable membrane. There is a cavity within the head of the
toothbrush below the membrane, such that the bristles are resiliently
forced into the head as the bristles are applied to the teeth. This
20 independent motion of the bristles, in one plane, will not cause them to
conform to the sloping, arcuate, surfaces of the teeth.

U.S. Patents 5,355,546, 5,483,722 and 5,839,149 disclose
toothbrushes whose head is formed of a rigid frame supporting a flexible
25 resilient member which has a series of linearly parallel lines or arrays of
bristle tufts, which lines of bristle tufts are oriented along the
longitudinal axis of the toothbrush. In each of the these patents the
parallel lines of bristles are flexibly mounted, such that in brushing
when a tooth is forced against the center line of tufts, that line of tufts
30 will yield away from the tooth, causing the adjacent lines of bristle tufts
to orient themselves about the sides of the tooth. As this contouring

about the tooth is in two dimensions, these patents fail to address the overall three dimensional curvature of the teeth, especially the deep "v" shaped interproximal area between one tooth and the next.

5 U.S. Patent 5,651,158 discloses a flexible head toothbrush having many embodiments, including a first embodiment in which the bristles may be mounted on head segments linked by grooves or thinned, i.e. flexible, connections which may be filled with a resilient elastomer. A second embodiment comprises a toothbrush head having bristle
10 mounting segments within a hard peripheral frame, the segments being linked at planar points located 90° to the longitudinal axis of the handle, the linkage being of thinned sections such that the segments may be made to rock about these links, in addition to flexing. A third embodiment includes a hard peripheral frame containing a toothbrush
15 head formed of one or more chains of bristle carriers, flexibly and resiliently linked to each other and linked to at least one end of the frame. A fourth embodiment is formed of segments which are not joined to each other, but are flexibly and resiliently linked to the handle or to the frame, wherein the linkage to the frame may be by thinned sections
20 or spines. In each embodiment the various segments or bristle carriers will flex independently or at most in coordination with the adjacent segments or bristle carriers within the chain of bristle carriers; such limited coordination of the orientation of the bristle tufts about the tooth will not provide the conformation to the various arcuate surfaces of the
25 tooth surfaces necessary for effective cleaning.

There is a need for a toothbrush, wherein the bristles coordinate their orientation to conform to the three dimensional arcuate tooth surfaces and the deep "v" shaped interproximal area between one tooth and the
30 next, such as to provide effective overall cleaning.

SUMMARY OF THE INVENTION

The present invention encompasses a toothbrush having bristle tufts which are capable of enhanced conformity to the arcuate tooth surfaces, said toothbrush
 5 comprised of a handle having a longitudinal axis and at one end thereof a head containing a plurality of bristle tufts extending therefrom; which head has a surrounding rigid periphery with an aperture extending therethrough and across which is a lattice or open network of flexibly resilient spines; wherein, each bristle tuft is anchored to said head at a node formed by the intersection of said spines. The lattice
 10 has a portion which is free of spines, this portion being located central to the head and on each side of the longitudinal axis, such that the lattice segments on each side of the longitudinal axis will flex independently. Each lattice segment flexes such that during brushing, as a tooth is forced against a bristle tuft, that bristle tuft will yield into the aperture and the immediate surrounding bristle tufts will tend to deflect toward that
 15 particular tooth, such deflecting bristle tufts conforming about the arcuate, three dimensional, surfaces of the particular tooth for more effective cleaning thereof.

In one aspect, the present invention provides a toothbrush having bristle tufts capable of providing enhanced conformity to arcuate tooth surfaces, comprising:

- 20 a handle having a longitudinal axis and a head at one end thereof, which head contains a face having a plurality of said bristle tufts extending therefrom;
 said face having a rigid periphery, within which rigid periphery is an aperture extending therethrough;
 a network of flexibly resilient spines forming a lattice extending across said
 25 aperture and attached to said rigid periphery;
 said lattice having a center portion which is free of said spines;
 said lattice having nodes located at the intersection of said spines, each node having one of said bristle tufts anchored therein.

30 In another aspect, the present invention provides a toothbrush exhibiting enhanced conformity to arcuate tooth surfaces for enhanced cleaning, comprising:

- a handle having a longitudinal axis and a head at one end thereof, which head contains a face having a plurality of bristle tufts extending therefrom;
 said face having a rigid periphery, to which rigid periphery is attached a network
 35 of flexibly resilient spines forming a lattice extending across said face;
 said lattice having a center portion which is free of said spines;

said lattice having nodes located at the intersection of the spines, each node having one of said bristle tufts anchored therein;

said head having a concave portion therein, beneath said lattice and extending
5 across said head.


In yet another aspect, the present invention provides a process for making a toothbrush, comprising:

- pre-forming bristle tufts by fusing the base of a plurality of bristles into a knob;
- 10 positioning the knobs of said pre-formed bristle tufts within a toothbrush mold;
- injecting flexibly resilient material about the knobs to form nodes, whereby the pre-formed bristle tufts are locked therein and wherein said flexibly resilient material forms spines connecting said nodes in a lattice across the face of said toothbrush;
- said lattice having a center portion which is free of any spines.

15

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side plan view, showing the toothbrush with a typical flat bristle pattern.



- 20 FIG. 2 is a front plan view of the toothbrush showing within the head section the network of bristle tuft carriers supporting the bristles shown in FIG. 1.



Fig. 3 is an enlarged front plan view of the toothbrush head shown in Fig. 2.

Fig. 4 is a section view, through section B-B of Fig. 3, showing in two dimensions the conformation of the bristles about the arcuate surfaces of a typical tooth.

Fig. 5 is a detail of the bristle tufts, showing the nodes within the network of bristle tuft carriers, i.e. the fused ends of the bristle tufts secured together by the connecting spines.

Fig. 6 is an alternate detail of the bristle tufts as shown in Fig. 5, i.e. the fused ends of the bristle tufts secured together by the connecting spines overmolded with an elastomer.

Detailed Description of the Invention

Referring now to the drawings, wherein like reference numerals refer to the same or similar elements among the several figures, and in particular to Figs 1 and 2; wherein there is shown a toothbrush, 10, in accordance with the present invention. Referring specifically to Fig. 2, a front plan view of such a toothbrush, 10, having head, 18, integral to a handle, 12, extending therefrom and a longitudinal axis, A-A, therethrough. The head, 18, contains a face, 14, which has a central concavity across which is a lattice or open network of flexibly resilient bristle carriers embodying the features and construction of this invention. Shown in Fig. 1, extending from the face, 14, are rows of bristle tufts, 16, transverse to the longitudinal axis A-A. Each bristle tuft, 16, is embedded and supported by at a node, 20, which as can be seen in Fig. 3, is formed at the junction at which the structural elements or spines, 22, of the network intersect.

As in Fig. 3, the face of the toothbrush of the present invention, 14, has a peripheral frame or rigid periphery, 24, the rigid periphery defining an opening or aperture extending through the toothbrush head, 18.

5 Alternatively, the toothbrush can also be formed with a closure across the back of the toothbrush head in the form of a concave segment below and separated from the lattice. In the case where the back of the toothbrush is enclosed, the concavity below the lattice can extend from 50 to 80% of the distance from the face to back, i.e. the depth of the

10 toothbrush head, which depth is up to about $\frac{1}{4}$ of an inch. The deflection of the bristle carriers into the concavity, during brushing, is illustrated by Fig. 4, which is a cross-section B-B of Fig. 3, perpendicular to the longitudinal axis A-A of the toothbrush. Fig. 4 only illustrates the conformation of the bristles about the tooth in two dimensions with the

15 deflection of the center bristle, 26, in the direction of the arrow in Fig. 4. However, the deflection of the center bristle, 26, will not only cause the bristles perpendicular to the longitudinal axis A-A to deflect toward and conform to the tooth; but, also the adjacent bristles parallel to the longitudinal axis will deflect toward and conform about the tooth

20 providing the present inventions three dimensional conformity to the tooth for effective cleaning thereof.

Further, within the present invention the lattice of spines extending across the face, 14, of the toothbrush has a central portion free of said

25 spines, such that the spines located central to the head, 18, and parallel to the longitudinal axis, A-A, do not intersect, i.e. are not connected (see Fig. 3). This discontinuity within the lattice allows the separate tuft supporting network segments, on each side of the longitudinal axis, to move independently. Such independent movement of the tuft supporting

30 network segments facilitates the toothbrushes simultaneous cleaning of different teeth and areas of the dentiture as occurs during brushing.

The head, 18, comprised of the neck, the peripheral frame, 24, and the lattice or network of flexibly resilient bristle carriers is preferably integral with the toothbrushes handle, 12, i.e. molded or otherwise formed as a single piece. The periphery of the head, 24, is at least 1/32 of an inch in width, and preferably at least 1/16 of an inch in width, so as to be rigid enough to adequately support the network of bristle tuft carriers, 20, attached thereto.

The network of bristle tuft carriers, including the spines, 22, and nodes, 20, are of a flexible and resilient material, preferably of polypropylene. Alternatively, the spines, 22, can be of polyethylene or thermoplastic elastomer (TPE), or a combination thereof. The degree of flexibility and resilience of the spines, 22, can be further controlled by varying their dimensions, e.g. reducing the depth or thickness of each spine, 22, to provide additional flexibility or by providing an overcoating of a second elastomer about each spine, 22, and node, 20, as illustrated in Fig. 6. Acceptable TPE materials, including a thermoplastic vulcanate (TPV) which consists of a mixture of polypropylene and EPDM (ethylene propylene diene monomers) which is available as Santoprene (brand), described in U.S. Patent 5,393,796; or Vyram (brand), another TPV consisting of a mixture of polypropylene and natural rubber, both Santoprene and Vyram being elastomers marketed by Advanced Elastomer Systems LP, Akron, Ohio 44311. Another, and preferred TPE is Dynaflex G6713 (brand), marketed by GLS Corp., Cary, Illinois 60013. These and other suitable elastomers have, typically, a Shore A hardness of from about 13 to 94, with about 29 being a preferred hardness.

Toothbrushes today are typically molded of polypropylene, in the present invention it is preferred that the lattice or network of bristle tuft carriers also be of polypropylene to facilitate one-step molding of the

toothbrush. If a clear appearance is desired, the handle, 12, head, 18, and lattice can be of polyester, such as polyethylene terephthalate. A preferred polypropylene is Huntsman Polypropylene 5520 (Brand), manufactured by the Huntsman Polypropylene Corporation, Hinsdale, Illinois 60521.

If desired, the toothbrush of the present invention can be molded as a "dual component" toothbrush, by which is meant that the flexibly resilient material of the bristle supporting network or lattice is of a material different than that of the hard plastic toothbrush head, 18, and handle, 12. The method of manufacture of such a dual component toothbrush by conventional dual component injection molding technology is well known in the art. For example, in accordance with the present invention, the lattice material may be introduced into the head area by a second injection step, after that used for the injection molding of the hard bristle implanting head and handle. In this second injection step the semi-finished toothbrush is positioned in a second mold into which the lattice material is injected about the interior of the rigid periphery, 24. To increase the surface area for the elastomer to adhere to the rigid periphery, 24, for increased adhesion thereto, a groove or recess can be provided about the upper surface of the interior of the rigid periphery.

A one-step molding process can be utilized in the manufacture of toothbrushes of the present invention, when the head, 18, contains an aperture extending therethrough and when the lattice is of the same material as the remainder of the toothbrush frame, i.e. the head, 18, and handle, 12. In contrast, a two-step molding process must be used whenever the head, 18, of the toothbrush contains a concavity below the lattice, this concavity is formed by the toothbrush having an enclosed back, such enclosure being separated from the lattice. In such a two-

step molding process, the toothbrush frame and integral lattice are formed in a first injection mold and the semi-finished toothbrush is repositioned in a second injection mold, wherein the back enclosure is formed.

5

Facilitation of two step injection molding of toothbrushes of the present invention can be by using a two component mold. Two component molds are available from Machines Boucherie N.V., Izegem, Belgium; which molds can be mounted in typical injection molding machines for such implementing the two step injection process, such
10 machines including 300 ton, two component injection molding machines available from Engel Canada, Inc., Guelph, Ontario.

The toothbrush bristles may be implanted as the nodes of the flexibly resilient elastomeric material of the bristle supporting network are
15 formed using non-staple, in-mold tufting (IMT) technology as disclosed in U.S. Patents 5,609,890, 5,390,984, and 5,533,791. Such IMT technology involves a process and the associated machinery wherein each tuft of bristles is first pre-formed into an assembly by fusing its base of bristles
20 together into a knob. This knob is then held in the mold into which the flexibly resilient material of the bristle supporting network or lattice is injected, such that the material flows about the knob, anchoring the tuft into place within the toothbrush face, 14. Fig. 5 illustrates finished IMT tufts of bristles, 16; wherein, the material of the bristle supporting
25 network, i.e. the spines, 22, surrounds and anchors the knob, 28, at the base of each bristle tuft, 16.

Any discussion of documents, acts, materials, devices, articles or the like which has been included in the present specification is solely for the purpose of providing a context for the present invention. It is not to be taken as an admission that any or all of these matters form part of the prior art base or were common general knowledge in the field relevant to the present invention as it existed before the priority date of each claim of this application.

Throughout this specification the word "comprise", or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated element, integer or step, or group of elements, integers or steps, but not the exclusion of any other element, integer or step, or group of elements, integers or steps.



THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A toothbrush having bristle tufts capable of providing enhanced conformity to arcuate tooth surfaces, comprising:
 - 5 a handle having a longitudinal axis and a head at one end thereof, which head contains a face having a plurality of said bristle tufts extending therefrom;
 - said face having a rigid periphery, within which rigid periphery is an aperture extending therethrough;
 - a network of flexibly resilient spines forming a lattice extending across said
 10 aperture and attached to said rigid periphery;
 - said lattice having a center portion which is free of said spines;
 - said lattice having nodes located at the intersection of said spines, each node having one of said bristle tufts anchored therein.
 - 15 2. The toothbrush of claim 1, wherein the rigid periphery is at least 1/32 of an inch in width.
 3. The toothbrush of claim 1 or claim 2, wherein the spines are of a flexible and resilient material selected from the group consisting of polypropylene, polyethylene, a
 20 thermoplastic elastomer and a combination thereof.
 4. A toothbrush exhibiting enhanced conformity to arcuate tooth surfaces for enhanced cleaning, comprising:
 - a handle having a longitudinal axis and a head at one end thereof, which head
 25 contains a face having a plurality of bristle tufts extending therefrom;
 - said face having a rigid periphery, to which rigid periphery is attached a network of flexibly resilient spines forming a lattice extending across said face;
 - said lattice having a center portion which is free of said spines;
 - said lattice having nodes located at the intersection of the spines, each node
 30 having one of said bristle tufts anchored therein;
 - said head having a concave portion therein, beneath said lattice and extending across said head.
 5. The toothbrush of claim 4, wherein the concave portion can extend from 50 to
 35 80% of the depth of the toothbrush head.

6. The toothbrush of claim 4 or claim 5, wherein the rigid periphery is at least 1/32 of an inch in width.

7. The toothbrush of any one of claims 4 to 6, wherein the spines are of a flexible
5 and resilient material selected from the group consisting of polypropylene, polyethylene, a thermoplastic elastomer and a combination thereof.

8. A process for making a toothbrush, comprising:
pre-forming bristle tufts by fusing the base of a plurality of bristles into a knob;
10 positioning the knobs of said pre-formed bristle tufts within a toothbrush mold;
injecting flexibly resilient material about the knobs to form nodes, whereby the pre-formed bristle tufts are locked therein and wherein said flexibly resilient material forms spines connecting said nodes in a lattice across the face of said toothbrush;
said lattice having a center portion which is free of any spines.

15 9. A toothbrush having bristle tufts capable of providing enhanced conformity to arcuate tooth surfaces substantially as hereinbefore described with reference to any one of the Figures 2 to 6.

20 Dated this eighth day of April 2003

Colgate-Palmolive Company
Patent Attorneys for the Applicant:

F B RICE & CO

1/2




Fig. 1




Fig. 2

2/2




Fig. 3




Fig. 4




Fig. 5




Fig. 6